



HOUSING:	High impact glass reinforced polyester	DMC45 Indoor Plastic Shell Metering Current Transformer				
SYSTEM VOLTAGE:	1100 Volts					
SYSTEM FREQUENCY:	50Hz					
TEST VOLTAGE POWER FREQUENCY:	3KV RMS for 1 minute	VA Ratings to relevant standard and classes				
Ith	60/100 times for 1 sec.		AS:60044-1:2007 IEC185:1986		AS:60044-1:2007 AS1675:1986	
INSULATION:	Class E	RATIO	CLASS 3	CLASS 1	CLASS 2	CLASS 1
SERVICE TEMPERATURE:	20c TO 120c	200/5	10	7.5	7.5	5
STANDARDS COMPLIANCE:	The DMC Range of Current Transformers complies with the following Standards; AS:1675:1986 IEC:185:1986 BS3938:1982 AS:60044-1:2007	250/5	10	10	10	7.5
		300/5	15	10	10	7.5
		400/5	20	15	10	7.5
		500/5	20	15	15	10
		600/5	25	15	15	10
		750/5	30	15	15	15
		800/5	30	15	15	15

For applications outside the range shown including; • 1 Amp Secondaries
 • Protection Classes
 • Multi - Core Assemblies

Please refer to STEMAR Sales Dept.



Stemar Electrical Products Pty. Ltd. ABN 13 067 330 269

243 Milperra Rd
 P.O. Box 538
 REVESBY NSW 2212
 Australia

Phone: (61 2) 9771 2100
 Fax: (61 2) 9774 5585
 Email: sales@stemar.com.au
 Web: www.stemar.com.au

