



HOUSING:	High impact glass reinforced polyester	DMC60 Indoor Plastic Shell Metering Current Transformer				
SYSTEM VOLTAGE:	1100 Volts					
SYSTEM FREQUENCY:	50Hz					
TEST VOLTAGE POWER FREQUENCY:	3KV TMS for 1 minute	VA Ratings to relevant standard and classes				
Ith	60/100 times for 1 sec.		AS:60044-1:2007 IEC185:1986		AS:60044-1:2007 AS1675:1986	
INSULATION:	Class E	RATIO	CLASS 3	CLASS 1	CLASS 2	CLASS 1
SERVICE TEMPERATURE:	20c TO 120c	200/5	15	10	10	7.5
STANDARDS COMPLIANCE:	The DMC Range of Current Transformers complies with the following Standards; AS:1675:1986 IEC:185:1986 BS3938:1982 AS:60044-1:2007	250/5	15	10	10	10
		300/5	20	15	15	7.5
		400/5	25	15	15	7.5
		500/5	25	15	15	10
		600/5	25	15	15	10
		750/5	30	20	20	10
		800/5	30	20	20	15
		1000/5	30	25	25	15

- For applications outside the range shown including;
- 1 Amp Secondaries
 - Protection Classes
 - Multi - Core Assemblies

Please refer to STEMAR Sales Dept.



Stemar Electrical Products Pty. Ltd. ABN 13 067 330 269

243 Milperra Rd
P.O. Box 538
REVESBY NSW 2212
Australia

Phone: (61 2) 9771 2100
Fax: (61 2) 9774 5585
Email: sales@stemar.com.au
Web: www.stemar.com.au

